




192 Y STRAINER



Suitable for domestic water services, heating and air-conditioning PLANTS, COMPRESSED AIR SYSTEMS.



Female/female threads and inspection plug Body in brass

Minimum and maximum working temperatures:

-20°C, 110°C in absence of steam


Degree of filtration: 1/4" through 2" 500μm, 2.1/2", 3", 4" 800μm Threads: ISO228 (equivalent to DIN259 and BS2779)

SIZE	1/4"	3/8"	1/2"	3/4"	1"	1″1/4	1″1/2	2"	2″1/2	3"	4"
A (mm)	55	55	58	70	87	96	106	126	150	169	219
B (mm)	40	40	40	48	56	64	73	89	107	120	161
DN	8	10	15	20	25	32	40	50	65	80	100
working PRESSURE kg/cm² bar	20	20	20	20	20	20	20	20	16	16	16
WORKING PRESSURE psi	290	290	290	290	290	290	290	290	240	240	240

193 NICKEL-PLATED Y STRAINER



SUITABLE FOR DOMESTIC WATER SERVICES, HEATING AND AIR-CONDITIONING PLANTS, COMPRESSED AIR SYSTEMS.



Female/female threads and inspection plug Body in nickel-plated brass Minimum and maximum working temperatures:

-20°C, 110°C in absence of steam

Available in 3 degrees of filtration: 500µm, 300µm, 50µm Threads: ISO228 (equivalent to DIN259 and BS2779)

SIZE	1/4"	3/8"	1/2"	3/4"	1″	1″1/4	1″1/2	2"
A (mm)	55	55	58	70	87	96	106	126
B (mm)	40	40	40	48	56	64	73	89
DN	8	10	15	20	25	32	40	50
working Pressure kg/cm² bar	20	20	20	20	20	20	20	20
WORKING PRESSURE PSI	290	290	290	290	290	290	290	290