Plastic Waste Pipe and Fittings
Chrome Plated Brass Waste Pipe and Fittings
Drain Connectors
Aluminium Roof Flashing (MacFlash)



SECTION

3

перейти на сайт: www.san-detal.ru



Multifit Waste Fittings



11/4"	11/2"	2"
Code	Code	Code

90° Bend





90° Bend Multifit x European pipe size

x 32mm x 40mm x	50mm



90° Bend Multifit x 32mm European pipe size Ring Seal **Pushfit**

MS4-32MM	-	-
-----------------	---	---



90° Bend Solvent Weld x 32mm European pipe size Ring Seal **Pushfit**

MS4-32SOLVENT



90° Bend Multifit x Plain End*

MS4L	MT4L	MZ4L



135° Bend

	MS20	MT20	MZ20
--	------	------	------



135° Bend Multifit x Plain End*

MS20L	MT20L	MZ20L
MOZUL	IVITZUL	MAZZUL



Straight Connector

S28M	T28M	Z28M



Straight Connector 11/4" x 11/2"

- ST28M -



Code Code Code **Straight Connector** Multifit x European pipe size

11/2"

2"

11/4"

ST28L-ISO	-	-
x 40mm	-	-
S28L-ISO	T28L-ISO	Z28L-ISO
x 32mm	x 40mm	x 50mm
	1	

Adjustable Straight Connector



MS18E MT18E MZ18E



Straight Connector Multifit x Plain End*

MS18L	MT18L
IAIDTOL	IVITOL



Swept Tee

V8M V1M V15M



1½" Equal Slip Tee with **Universal Connections**

-	V1MX	-



Reducer for Fittings*



1½" x 1¼" **T12M** 2" x 1¹/₄" ZS26L 2" x 1½" ZT26L





2" x 19/23mm -TUN-2


48

Multifit Waste Fittings









S21A

T21A

Z21A



Flexible Waste Fittings

Flexible Connector offers maximum flexibility when conventional Fittings cannot be used

- Maximum effective length 18"
- Plain Spigot to suit Multifit and Universal Outlet Traps or Waste Fittings
- Universal Outlet Connection



FLEXCON1	FLEXCON2	-
Code	Code	Code
11/4"	1½"	2"

Flexible Fittings

 These Fittings offer complete flexibility for any required angle or offset



Universal Connection x Universal Connection

FLEXCON3 FLEXCON4 FLEXCON7

Universal Connection x PVC Plain Spigot to BS EN 1329-1:2000

FLEXCON5 FLEXCON6 FLEXCON8

Non-Return Valves and Sundry

Non-Return Valves



 $1\frac{1}{4}$ " $1\frac{1}{2}$ " 2" Code Code

In-Line Non-Return Valve with 1½" Multifit Connections and top access for cleaning

T28M-NRV



In-Line Non-Return Valve with 2" Universal Connections and top access for cleaning

- - Z28M-NRV



In-Line Non-Return Valve with 2" BS EN 1329-1:2000 Solvent Weld Connections and top access for cleaning

- **Z28M-NRVS**

 Non-Return Valves are designed to prevent a back flow of water. They must only be used when there is no alternative and on the basis that they are cleaned regularly

Sundry Fittings



90° Bend with BSP male thread x BSP coupling nut

T1

Z1

Z8A

Z8B

BSP Nut Ordinary

S8A T8A

BSP Nut Compression

S8B

S1



Compression Ring for Imperial

T₈B

S13 T13 -



BSP Coupling to BS EN 1329-1:2000 ABS or PVC pipe, must be solvent welded

S25 T25 -

50



11/4"	11/2"	2"
Code	Code	Code

Trap Inlet Reducer

11/4" x 1"

S16 1½" x 1¼" **T16**



Blank Cap with nut for BSP threads

S23	T23	Z23

11/4" 11/2" Code Code 7" Extension Piece effective length 5". Available longer or shorter on application **S22L T22L**

Mechanical Soil and Rainwater Pipe Boss Connectors



Mechanical Soil and Rainwater Pipe Boss Connector for 11/4" pipe



Code BOSSCONN1.25BL Code **BOSSCONN1.25GR**



Reducer in ABS 11/4" Plain Tail x 19/23mm Universal Connection



Code R16-BL Code **R16-GR**



Mechanical Soil and Rainwater Pipe Boss Connector for 19/23mm pipe



BSP Female x BSP Male Couplings



	1 ½"	1 ½"
	Code	Code
BSP Coupli	ng	
1" length	S12A-1	T12A-1
2" length	S12A-2	T12A-2
3" length	S12A-3	T12A-3



BSP Coupling Flush Spigot European to UK Waste Adaptor

S12Δ-F	T12Δ-F
312A-I	



BSP Coupling

1½" x 1"	512C	
1" x 3/4"	\$12D	



BSP Coupling Waste Outlet Reducer

1½" x 1¼"	-	T12



BSP Coupling

$1^{3}/_{4}$ " x $1^{1}/_{2}$ "	-	T12B
2" x 1½"	-	T12C
2" x 11/4"	-	T12D
1½" x 1"	-	T12H



BSP Coupling

1½" x 2"	-	T12E
1½" x 1¾"	-	T12F

Chrome Plated Brass Waste Pipe and Fittings

	32mm Code	35mm Code		42mm Code
	1m length of CP Brass Pi			Code
7	European pipe size	1¾" UK pip	e size	1½" UK pipe size
	PIPE32-1000-CB	PIPE35-100	0-CB	PIPE42-1000-CB
J.	90° Compression Bend			
	32A-CB	35A-CE	}	42A-CB
	135° Compression Bend			
	<u>-</u>	35B-CB	}	42B-CB
	Compression Tee			
	-	-		42E-CB
	Compression Straight Co	nnector		
	32G-CB	35G-CE	3	42G-CB
6	Wall Flange			
	WALLFLANGE-CP32	WALLFLANGE	-CP35	WALLFLANGE-CP42
	Synthetic Rubber Seal Re	ducers for abov	e Fittings	
		R/SEAL-35		R/SEAL-42X32
	N			R/SEAL-42X35
	ABS Solvent Weld Adapto plastic solvent weld waste		ve Fittings	to BS EN 1329-1:2000
	ABSCON-32X1.25	ABSCON-35	X1.25	ABSCON-42X1.5
	Bend 1¼" Multifit x 32mm pean pipe size			d 1¼" Multifit x 32mr n pipe size Ring Seal
Code	MS4-ISO		Code	MS4-32MM
	ght Connector 1¼" Multifit mm European pipe size			d 1¼" Solvent Weld x uropean pipe size Rin

■ For Multifit Fittings suitable for use with 35mm and 42mm external diameter pipe see pages 48 and 49

S28L-ISO

Seal Pushfit

MS4-32SOLVENT

Code

■ For Chrome Plated Traps see pages 6, 7 and 18

Code



11/4"	1 ¹ / ₂ "	2"
Code	Code	Code

HDPE White Pipe 3m lengths

HD1-3M HD2-3M HD3-3M



Pipe C	lip
--------	-----

S30	T30	Z 30



90° Bend

S4L T4L -



135° Bend

S20L	T20L	-
------	------	---



Straight Connector



Straight Connector Multifit x
Surefit

S28L	T28L	Z28L
------	------	------



Reducer 11/2" to 11/4"

-	T12L	-



Blank Cap without nut

S23L 1	Γ23L	Z23L
--------	------	-------------



Reducer for Fittings

2"-11/4"	11/2"-11/4"	2"-11/2"
S26L	T12S	T26L



11/4"	11/2"
Code	Code

Swept Tee

V8L V1L



Swept Tee

$1\frac{1}{2}$ " x $1\frac{1}{2}$ " x $1\frac{1}{4}$ " - V21	$x 1\frac{1}{2}$ " $x 1\frac{1}{4}$ " -	V21L
---	---	------



Swept Tee Surefit x 19mm pushfit branch

1½" x 1½" x ¾"	-	V23L
1½" x 1½" x 3½"	V24L	-



Swept Tee BSP nut x BSP thread x Nozzle for discharge hose of domestic appliance

1½" x 1½" x ¾"	-	V33L
1½" x 1½" x 3½"	V34L	-



Tee Piece BSP nut x BSP thread x 135° Nozzle for discharge hose of domestic appliance

1½" x 1½"	V33S	
11/4"	11/2"	2"
Code	Code	Code



90° Connector to soil pipe boss BS EN 1451-1:2000 size*

S4M	T4M	_



135° Connector to soil pipe boss BS EN 1451-1:2000 size*



Straight Connector to soil pipe boss BS EN 1451-1:2000 size*

S18M	T18M	Z18M
------	------	-------------



Flange for HDPE Pipe

S17	T17	-

- *BS 5254 size if connecting to boss size BS 5255 add 5255 to code e.g. S4M 5255
- Surefit Waste Fittings only suitable for M^CAlpine HDPE Waste Pipe

Drain Connectors and Blanking Off Caps



4"/110mm x 4"/110mm Connector with 'O' Seal Socket to fit 4"/110mm Ø pipe to BS 4514 Colour: Black DC1-BL

Colour: Grey

DC1-GR



4"/110mm x 11/4" and 11/2" **Connector** with Sealing Ring to fit $1\frac{1}{4}$ " and $1\frac{1}{2}$ " plastic waste pipe to BS EN 1451-1:2000 and BS EN 1329-1:2000

Code

DC2-BL



4"/110mm x 11/4" and 11/2" **Connector** with Offset Sealing Ring to fit 11/4" and 1½" plastic waste pipe to BS EN 1451-1:2000 and BS EN 1329-1:2000

Code


DC2BL-OS



4"/110mm x 2" Connector with Sealing Ring to fit 2" plastic waste pipe to BS EN 1451-1:2000 and BS EN 1329-1:2000

Code

DC3-BL



4"/110mm x 2" Connector with Offset Sealing Ring to fit 2" plastic waste pipe to BS EN 1451-1:2000 and BS EN 1329-1:2000

Code

DC3BL-OS



4"/110mm Blank Cap suitable for sealing cast iron, plastic or clay 4"/110mm Ø pipe Code DC4-BL

Drain Connector with Boss

- Manufactured in polypropylene
- Finned seal spigot for internal connection to cast iron, plastic or clay 4"/110mm pipe
- Ideal for low level connections



4"/110mm x 4"/110mm Connector with 'O' Seal Socket to fit 4"/110mm Ø pipe to BS 4514 and 1¹/₂" Universal Pipe Boss including Blanking Cap

Colour: Black	DC1-BL-BO
Colour: Grey	DC1-GR-BO

Temporary Blanking Off Caps

Code



Synthetic Rubber Cap for 110mm Ø soil pipe

			_
11/4"	11/2"	2"	_
Code	Code	Code	



Synthetic Rubber Cap for waste pipe

CAP100

S23MR T23MR **Z23MR**

RS7

Aluminium Roof Flashing (MacFlash)

General

- MacFlash Aluminium Roof Flashing offers an alternative to traditional lead roof slates
- The Aluminium Flashing is manufactured from high grade aluminium and the Collar from synthetic rubber, both to British Standards. The Collar is die-formed to the Aluminium Flashing

Advantages

Code

■ MacFlash is quickly and easily installed and offers cost savings in material and labour

RS2

- MacFlash is suitable for flat roofs and for roof pitches up to 45°
- MacFlash has special corrugations that can be easily dressed to form a seal
- MacFlash can be used with flue pipes from condensing boilers

Nominal Pipe Size 4"/110mm pipe Base Measurements 18" x 18"		Nominal Pipe Size 3"/75mm pipe Base Measurements 18" x 18"		
Code	RS1	Code	RS4	
Nominal Pipe Size 4"/110mm pipe Base Measurements 18" x 24"		Nominal Pipe Size 2"/50mm pi Base Measurements 18" x 18"	pe	

Code

Nominal Pipe Size 4"/110mm pipe Base Measurements 24" x 24"

Code RS3

